

AVAILABLE MODELS:

COMMON FEATURES OF THE SERIES:

- Enclosure with hinged closet panel. Side fixed panel as an option.
- 6 mm thick safety glass.
- Profile finishes depending on enclosure configuration.
- Base profile and multi-position stabilizer bar in Chrome and Black.
- Turin handle in Chrome and Black as standard.
- Profile to wall with offset up to 20 mm.
- 15 mm fixed side panel offset.
- Equipped with overlap lock.
- 6 mm partition fixed separator panel and in acid finish.
- Cabinet with two shelves and cover in acid finish as standard. Fixed shelves as standard and height-adjustable as an option at no extra charge.
- Teknoclean as standard.

FINISHES:

- Anodized profiles in champagne, gold, black y copper.

COMPOSITION/MATERIALS:

Profiles:Aluminium. Alloy 6063
Metallic pieces:Zamak, Steel
Chromed plastic covers:ABS
Transparent plastic lids:ABS
Rollers:Steel ball bearings, brass inside track, POM outside track
Seals:PVC

TESTS:

The KONVERT collection complies with the European standard EN 14428, exceeding all the tests stipulated therein, as detailed below.

Characteristic to be tested	Assessment method	Compliance criteria	Apt
Cleanability	Visual examination. (4.2)	Free from sharp corners, edges and burrs. (4.2)	✓
Impact resistance / shatter properties	R100, 40 particles minimum. (5.1, 5.2)	Thermally toughened safety glass. (4.3)	✓
Corrosion resistance	240 hours in salt spray. (4.4.2)	Corrosion-proof. (4.4.2)	✓
Resistance to chemicals and stains	Reagents: acids, alkalis, alcohols,bleaches, staining agents. (5.3)	Not showing permanent staining or deterioration. (4.4.3)	✓
Resistance to wet and dry cycling	Wet and dry 50 cycles. (5.4)	Not showing any cracks, crazing or discoloration after 50 cycles. (4.4.4)	✓
Endurance	20.000 closing-opening cycles. (5.5)	Not showing any functional deterioration. (4.4.5)	✓
Stability	Resistance to impact. (5.6)	Resists the impact without any functional deterioration. (4.4.6)	✓
Water retention	Watertightness. (5.7)	Retains water. (4.4.7)	✓

QUALITY CERTIFICATES:



MODEL EXAMPLE:

