

AVAILABLE MODELS:

COMMON FEATURES OF THE SERIES:

- Bath screen with sliding panels.
- Fixed reversible joint.
- 3 mm safety glass.
- Fixed side 6 mm safety glass.
- Available in ACRYLIC.
- Profile compensation of 20 mm for each side and 25 mm for fixed side.
- Equipped with magnetic closure.
- Top guide with double bearing.
- Adjustable safety slider on the inside.
- Four bearings per blade.
- The outer leaf is on the right-hand side.
- Teknoclean included in glass.

FINISHES:

- Anodized profiles in white.

COMPOSITION/MATERIALS:

Profiles:Aluminium. Alloy 6063
 Metallic pieces:Zamak, Steel
 Chromed plastic covers:ABS
 Transparent plastic lids:ABS
 Rollers:Steel ball bearings, brass inside track, POM outside track
 Seals:PVC

TESTS:

The BACO collection complies with the European standard EN 14428, exceeding all the tests stipulated therein, as detailed below.

Characteristic to be tested	Assessment method	Compliance criteria	Apt
Cleanability	Visual examination. (4.2)	Free from sharp corners, edges and burrs. (4.2)	✓
Impact resistance / shatter properties	R100, 40 particles minimum. (5.1, 5.2)	Thermally toughened safety glass. (4.3)	✓
Corrosion resistance	240 hours in salt spray. (4.4.2)	Corrosion-proof. (4.4.2)	✓
Resistance to chemicals and stains	Reagents: acids, alkalis, alcohols,bleaches, staining agents. (5.3)	Not showing permanent staining or deterioration. (4.4.3)	✓
Resistance to wet and dry cycling	Wet and dry 50 cycles. (5.4)	Not showing any cracks, crazing or discoloration after 50 cycles. (4.4.4)	✓
Endurance	20.000 closing-opening cycles. (5.5)	Not showing any functional deterioration. (4.4.5)	✓
Stability	Resistance to impact. (5.6)	Resists the impact without any functional deterioration. (4.4.6)	✓
Water retention	Watertightness. (5.7)	Retains water. (4.4.7)	✓

QUALITY CERTIFICATES:



MODEL EXAMPLE:

