Brisse Swinging

PRODUCT DATA SHEET

profiltek®

AVAILABLE MODELS:



BRA-240

COMMON FEATURES OF THE SERIES:

- Bath and shower screen for bathtub with hinged panel or fixed plus hinged panel, with the option of inward and outward opening
- Toughened safety glass available in 6 or 8 mm.
- Profile finishes in Polished Silver, Black, Gold, Gunmetal, Copper, and Champagne.
- Lima handle as standard.
- For configurations with fixed panel, supplied with standard profile; optional with brackets. For hinged door configurations, supplied with standard hinge; optional with profiled hinge.
- Multi-position bar as standard. Optional perimeter bar.
- Wall fixing with profile allowing up to 15 mm adjustment.
- Fitted with magnetic closure or non-magnetic contact closure according to configuration. Closure with profile and concealed magnet.
- Flush hinges on the inside of the screen for easy cleaning.
- Eco-designed product.
- Teknoclean included.

FINISHES:

- Anodized profiles in champagne, gold, black, polished silver y copper.

COMPOSITION/MATERIALS:

Profiles: ..... Aluminium. Alloy 6063
Metallic pieces: ..... Zamak, Steel
Chromed plastic covers: ..... ABS
Transparent plastic lids: ..... ABS
Rollers: ..... Steel ball bearings, brass inside track, POM outside track
Seals: ..... PVC

TESTS:

The BRISSE SWINGING collection complies with the European standard EN 14428, exceeding all the tests stipulated therein, as detailed below.

Characteristic to be tested	Assessment method	Compliance criteria	Apt
Cleanability	Visual examination. (4.2)	Free from sharp corners, edges and burrs. (4.2)	✓
Impact resistance / shatter properties	R100, 40 particles minimum. (5.1, 5.2)	Thermally toughened safety glass. (4.3)	✓
Corrosion resistance	240 hours in salt spray. (4.4.2)	Corrosion-proof. (4.4.2)	✓
Resistance to chemicals and stains	Reagents: acids, alkalis, alcohols,bleaches, staining agents. (5.3)	Not showing permanent staining or deterioration. (4.4.3)	✓
Resistance to wet and dry cycling	Wet and dry 50 cycles. (5.4)	Not showing any cracks, crazing or discoloration after 50 cycles. (4.4.4)	✓
Endurance	20.000 closing-opening cycles. (5.5)	Not showing any functional deterioration. (4.4.5)	✓
Stability	Resistance to impact. (5.6)	Resists the impact without any functional deterioration. (4.4.6)	✓
Water retention	Watertightness. (5.7)	Retains water. (4.4.7)	✓

QUALITY CERTIFICATES:

kiwa CERTIFICADO ISO 14001 1918-9/23 ENAC
kiwa CERTIFICADO ISO 14006 1918-Z/22
kiwa CERTIFICADO ISO 56001 004/2008 ENAC
kiwa CERTIFICADO ISO 9001 1918-3/23 ENAC

MODEL EXAMPLE:



Brisse Swinging

PRODUCT DATA SHEET


profiltek®

WARNINGS!


/ Maximum height: 2200 mm. For Wavy glass finish, maximum height: 2000 mm.
/ Maximum width of the hinged leaf cannot exceed 1000 mm.
/ 15 mm adjustment with profile.
/ It is essential to indicate the mounting side when placing the order.
/ See types of closure according to configuration in the decorator.
/ For enclosures with a height under 1650 mm, the handle/knob height will be 600 mm. For heights above 1650 mm, the handle will be centered on the glass.
/ Minimum glass width for Imagik: 250 mm.
/ Custom Imagik available. Consult the technical feasibility of your proposal.
/ Any glass wider than 1200 mm or guides and profiles longer than 2200 mm will incur an additional surcharge due to special logistical conditions. See ßrice surcharges"on page 23.
/ No price surcharge applies for a bathtub height of 1500 mm.
/ VAT not included.

Technical details


BRA-240




BRA-205




BRA-206




BRA-207



BRA-208




BRA-210




BRA-213



BRA-216




BRA-220




*The plans and dimensions shown correspond to the standard product configuration. Any modification to the configuration may affect these dimensions.


Closing types




Magnetic closure



Magnetic closure



Magnetic closure



Magnetic closure