


Brisse Sliding

PRODUCT DATA SHEET

profiltek®

AVAILABLE MODELS:



COMMON FEATURES OF THE SERIES:

- Bath and shower screen with sliding panels.
- Minimalist design with concealed fixings.
- Profile finishes in Polished Silver, Black, Gold, Gunmetal, Copper, and Champagne.
- Capri handle as standard.
- Reduced vertical profiles with 10 mm adjustment per side.
- Fitted with contact or magnetic closing profile, depending on configuration.
- Progressive soft-close mechanism included as standard.
- Sliding panels without bottom track.
- Anti-tip system for panels.
- Panel release system included.
- Height-adjustable bearings (4 mm).
- Quick-fit installation system.
- Patented concealed bracket system.
- Eco-designed product.
- Teknoclean included.

FINISHES:

- Anodized profiles in champagne, gold, black, polished silver y copper.

COMPOSITION/MATERIALS:

Profiles:Aluminium. Alloy 6063
Metallic pieces:Zamak, Steel
Chromed plastic covers:ABS
Transparent plastic lids:ABS
Rollers:Steel ball bearings, brass inside track, POM outside track
Seals:PVC

TESTS:

The BRISSE SLIDING collection complies with the European standard EN 14428, exceeding all the tests stipulated therein, as detailed below.

Characteristic to be tested	Assessment method	Compliance criteria	Apt
Cleanability	Visual examination. (4.2)	Free from sharp corners, edges and burrs. (4.2)	✓
Impact resistance / shatter properties	R100, 40 particles minimum. (5.1, 5.2)	Thermally toughened safety glass. (4.3)	✓
Corrosion resistance	240 hours in salt spray. (4.4.2)	Corrosion-proof. (4.4.2)	✓
Resistance to chemicals and stains	Reagents: acids, alkalis, alcohols,bleaches, staining agents. (5.3)	Not showing permanent staining or deterioration. (4.4.3)	✓
Resistance to wet and dry cycling	Wet and dry 50 cycles. (5.4)	Not showing any cracks, crazing or discoloration after 50 cycles. (4.4.4)	✓
Endurance	20.000 closing-opening cycles. (5.5)	Not showing any functional deterioration. (4.4.5)	✓
Stability	Resistance to impact. (5.6)	Resists the impact without any functional deterioration. (4.4.6)	✓
Water retention	Watertightness. (5.7)	Retains water. (4.4.7)	✓

QUALITY CERTIFICATES:




MODEL EXAMPLE:



WARNINGS!

- / Maximum height: 2200 mm. For Wavy glass finish, maximum height: 2000 mm.
- / This shower enclosure allows direct installation in its final position over the shower tray.
- / Flush-fit tray may cause a change in the enclosure dimensions.
- / Minimum glass width for Imagik: 250 mm.
- / Custom Imagik available. Consult the technical feasibility of your proposal.
- / See price surcharges on page 23.
- / No price surcharge applies for a bath screen height of 1500 mm.
- / VAT not included.

Technical details



*The plans and dimensions shown correspond to the standard product configuration. Any modification to the configuration may affect these dimensions.

Closing types

