


AVAILABLE MODELS:



COMMON FEATURES OF THE SERIES:

- Bathtub and shower enclosure with sliding and fixed panels.
- 6 mm safety glass.
- Profile finishes in White, Silver, Polished Silver, Chrome and Black.
- Mónaco handle in Chrome and Black finish as standard.
- 20 mm profile offset on each side.
- Soft closure included in models EL-210 and EL-216.
- Equipped with magnetic or contact closure according to configuration.
- Sliding panel release system, by means of the lower bearings, to make cleaning easier.
- Double train of bearings, adjustable in height by 4 mm.
- With lower guide.
- Anti-rollover system.
- Quick mounting system
- See series optional accessories.
- Teknoclean as standard.

FINISHES:

- Anodized profiles in white y black.

COMPOSITION/MATERIALS:

Profiles:Aluminium. Alloy 6063
Metallic pieces:Zamak, Steel
Chromed plastic covers:ABS
Transparent plastic lids:ABS
Rollers:Steel ball bearings, brass inside track, POM outside track
Seals:PVC

TESTS:

The ELMA collection complies with the European standard EN 14428, exceeding all the tests stipulated therein, as detailed below.

Characteristic to be tested	Assessment method	Compliance criteria	Apt
Cleanability	Visual examination. (4.2)	Free from sharp corners, edges and burrs. (4.2)	✓
Impact resistance / shatter properties	R100, 40 particles minimum. (5.1, 5.2)	Thermally toughened safety glass. (4.3)	✓
Corrosion resistance	240 hours in salt spray. (4.4.2)	Corrosion-proof. (4.4.2)	✓
Resistance to chemicals and stains	Reagents: acids, alkalis, alcohols,bleaches, staining agents. (5.3)	Not showing permanent staining or deterioration. (4.4.3)	✓
Resistance to wet and dry cycling	Wet and dry 50 cycles. (5.4)	Not showing any cracks, crazing or discoloration after 50 cycles. (4.4.4)	✓
Endurance	20.000 closing-opening cycles. (5.5)	Not showing any functional deterioration. (4.4.5)	✓
Stability	Resistance to impact. (5.6)	Resists the impact without any functional deterioration. (4.4.6)	✓
Water retention	Watertightness. (5.7)	Retains water. (4.4.7)	✓

QUALITY CERTIFICATES:



MODEL EXAMPLE:

