
Specials

PRODUCT DATA SHEET

profiltek®

AVAILABLE MODELS:



ES-216 ES-215 ES-219 ES-218 ES-210 ES-213 ES-214 ES-225

COMMON FEATURES OF THE SERIES:

- Discover our series of special enclosures, where customization knows no limits. From unusual configurations to customization adapted to any style offering made-to-measure solutions that adapt perfectly to the shower space. Versatility and originality come together to create shower enclosures beyond conventional limits.
- Apart from the innovative configurations you'll find in our series of special shower enclosures, we want to emphasize that we are ready to take your ideas to the next level. Do you have a unique project in mind? We love challenges. Whatever your vision is, we're here to bring it to reality.

FINISHES:

- Anodized profiles in white, black y polished silver.

COMPOSITION/MATERIALS:

Profiles: ..... Aluminium. Alloy 6063
Metallic pieces: ..... Zamak, Steel
Chromed plastic covers: ..... ABS
Transparent plastic lids: ..... ABS
Rollers: ..... Steel ball bearings, brass inside track, POM outside track
Seals: ..... PVC

TESTS:

The SPECIALS collection complies with the European standard EN 14428, exceeding all the tests stipulated therein, as detailed below.

Characteristic to be tested	Assessment method	Compliance criteria	Apt
Cleanability	Visual examination. (4.2)	Free from sharp corners, edges and burrs. (4.2)	✓
Impact resistance / shatter properties	R100, 40 particles minimum. (5.1, 5.2)	Thermally toughened safety glass. (4.3)	✓
Corrosion resistance	240 hours in salt spray. (4.4.2)	Corrosion-proof. (4.4.2)	✓
Resistance to chemicals and stains	Reagents: acids, alkalis, alcohols,bleaches, staining agents. (5.3)	Not showing permanent staining or deterioration. (4.4.3)	✓
Resistance to wet and dry cycling	Wet and dry 50 cycles. (5.4)	Not showing any cracks, crazing or discoloration after 50 cycles. (4.4.4)	✓
Endurance	20.000 closing-opening cycles. (5.5)	Not showing any functional deterioration. (4.4.5)	✓
Stability	Resistance to impact. (5.6)	Resists the impact without any functional deterioration. (4.4.6)	✓
Water retention	Watertightness. (5.7)	Retains water. (4.4.7)	✓

QUALITY CERTIFICATES:

kiwa CERTIFICADO ISO 14001 1918-9/23 CERTIFICADORA ACREDITADA POR ENAC
kiwa CERTIFICADO ISO 14006 1918-Z/22
kiwa CERTIFICADO ISO 56001 004/2008 CERTIFICADORA ACREDITADA POR ENAC
kiwa CERTIFICADO ISO 9001 1918-3/23 CERTIFICADORA ACREDITADA POR ENAC

MODEL EXAMPLE:



Specials

PRODUCT DATA SHEET


profiltek®

WARNINGS!


/ Maximum height: 2200 mm. In Chrome finish, maximum height: 2000 mm.
/ Magnetic or non-magnetic contact closures depending on the configuration.
/ Equipped with base profile.
/ Angled profile available subject to prior technical feasibility study.
/ Rubber sealing system integrated in the hinge profile.
/ Folding panels are supplied with equal dimensions.
/ It is essential to indicate the anchoring side in the order. For models combining fixed panels and a door, the measurement of each element must be specified.
/ For any made-to-measure or special shower enclosure not included in the price list, please send the information and dimensions defining the desired model. The technical department will assess its feasibility before providing a quotation and delivery time.
/ Minimum glass width for Imagik: 250 mm.
/ Custom Imagik. Please consult the technical feasibility of your proposal.
/ Any glass over 1200 mm or guides and profiles over 2200 mm will incur an additional surcharge due to special logistical conditions. See "price list surcharges" on page 23.
/ VAT not included.

Technical details


ES-216




ES-215




ES-219




ES-218




ES-210



ES-213



ES-214




ES-225




*The plans and dimensions shown correspond to the standard product configuration. Any modification to the configuration may affect these dimensions.

Closing types



Magnetic closure



Contact closure