Galilea

PRODUCT DATA SHEET

profiltek®

AVAILABLE MODELS:



GA-206 GA-216 GA-209 GA-213 GA-240

COMMON FEATURES OF THE SERIES:

- Bathtub and shower enclosure with fixed plus hinged panels available with outward and inward opening depending on configuration.
- Safety glass available in 8 mm.
- Matt White, Chrome, Black and Gold profile finishes.
- Berlín handle in Matt White, Chrome, Black and Gold finish as standard.
- For configurations with fixed panel multi-position stabilizer bars in Matt White, Chrome, Black and Gold finish included.
- Wall anchoring with profile offset up to 15 mm.
- Equipped with magnetic or contact closure according to configuration. Profile closure with hidden magnet.
- Hinges flush on the inside of the enclosure for easy cleaning.
- Base profile in Matt White, Chrome, Black and Gold.
- Check out optional accessories of the series.
- Teknoclean as standard.

FINISHES:

- Anodized profiles in gold y black.

COMPOSITION/MATERIALS:

Profiles: ..... Aluminium. Alloy 6063
Metallic pieces: ..... Zamak, Steel
Chromed plastic covers: ..... ABS
Transparent plastic lids: ..... ABS
Rollers: ..... Steel ball bearings, brass inside track, POM outside track
Seals: ..... PVC

TESTS:

The GALILEA collection complies with the European standard EN 14428, exceeding all the tests stipulated therein, as detailed below.

Characteristic to be tested	Assessment method	Compliance criteria	Apt
Cleanability	Visual examination. (4.2)	Free from sharp corners, edges and burrs. (4.2)	✓
Impact resistance / shatter properties	R100, 40 particles minimum. (5.1, 5.2)	Thermally toughened safety glass. (4.3)	✓
Corrosion resistance	240 hours in salt spray. (4.4.2)	Corrosion-proof. (4.4.2)	✓
Resistance to chemicals and stains	Reagents: acids, alkalis, alcohols,bleaches, staining agents. (5.3)	Not showing permanent staining or deterioration. (4.4.3)	✓
Resistance to wet and dry cycling	Wet and dry 50 cycles. (5.4)	Not showing any cracks, crazing or discoloration after 50 cycles. (4.4.4)	✓
Endurance	20.000 closing-opening cycles. (5.5)	Not showing any functional deterioration. (4.4.5)	✓
Stability	Resistance to impact. (5.6)	Resists the impact without any functional deterioration. (4.4.6)	✓
Water retention	Watertightness. (5.7)	Retains water. (4.4.7)	✓

QUALITY CERTIFICATES:

kiwa CERTIFICADO ISO 14001 1918-9/23 ENAC
kiwa CERTIFICADO ISO 14006 1918-Z/22
kiwa CERTIFICADO ISO 56001 004/2008 ENAC
kiwa CERTIFICADO ISO 9001 1918-3/23 ENAC

MODEL EXAMPLE:



Galilea

PRODUCT DATA SHEET


profiltek®

WARNINGS!


/ Maximum height: 2200 mm. In Chrome finish, maximum height: 2000 mm.
/ For shower enclosures over 1950 mm high, maximum W cannot exceed 750 mm.
/ 15 mm front compensation per side.
/ Anchor side must be specified in the order.
/ Angled profile available subject to prior technical feasibility study.
/ Shower enclosure setback determined by outer edge of base profile.
/ For enclosures under 1650 mm high, handle/knob height: 600 mm. For enclosures over 1650 mm high, handle centred on glass.
/ Clear seals as standard. For Black profile finish, Black seals available at extra cost.
/ Minimum glass width for Imagik: 250 mm.
/ Custom Imagik. Technical feasibility of proposal must be checked.
/ Any glass width over 1200 mm or guides/profiles over 2200 mm will incur additional charges due to special logistics. See "surcharges" on page 23.
/ NO surcharge applied for bath height 1500 mm.
/ VAT excluded.

Technical details


GA-206




GA-216




GA-209



GA-213




GA-240




*The plans and dimensions shown correspond to the standard product configuration. Any modification to the configuration may affect these dimensions.


Closing types



Profile with magnetic closure



Magnetic closure



Magnetic closure