Konvert

PRODUCT DATA SHEET

profiltek®

AVAILABLE MODELS:

COMMON FEATURES OF THE SERIES:

- Enclosure with hinged closet panel. Side fixed panel as an option.
- 6 mm thick safety glass.
- Profile finishes depending on enclosure configuration.
- Base profile and multi-position stabilizer bar in Chrome and Black.
- Turin handle in Chrome and Black as standard.
- Profile to wall with offset up to 20 mm.
- 15 mm fixed side panel offset.
- Equipped with overlap lock.
- 6 mm partition fixed separator panel and in acid finish.
- Cabinet with two shelves and cover in acid finish as standard. Fixed shelves as standard and height-adjustable as an option at no extra charge.
- Teknoclean as standard.

FINISHES:

- Anodized profiles in champagne, gold, black, polished silver y copper.

COMPOSITION/MATERIALS:

Profiles: ..... Aluminium. Alloy 6063
Metallic pieces: ..... Zamak, Steel
Chromed plastic covers: ..... ABS
Transparent plastic lids: ..... ABS
Rollers: ..... Steel ball bearings, brass inside track, POM outside track
Seals: ..... PVC

TESTS:

The KONVERT collection complies with the European standard EN 14428, exceeding all the tests stipulated therein, as detailed below.

Characteristic to be tested	Assessment method	Compliance criteria	Apt
Cleanability	Visual examination. (4.2)	Free from sharp corners, edges and burrs. (4.2)	✓
Impact resistance / shatter properties	R100, 40 particles minimum. (5.1, 5.2)	Thermally toughened safety glass. (4.3)	✓
Corrosion resistance	240 hours in salt spray. (4.4.2)	Corrosion-proof. (4.4.2)	✓
Resistance to chemicals and stains	Reagents: acids, alkalis, alcohols,bleaches, staining agents. (5.3)	Not showing permanent staining or deterioration. (4.4.3)	✓
Resistance to wet and dry cycling	Wet and dry 50 cycles. (5.4)	Not showing any cracks, crazing or discoloration after 50 cycles. (4.4.4)	✓
Endurance	20.000 closing-opening cycles. (5.5)	Not showing any functional deterioration. (4.4.5)	✓
Stability	Resistance to impact. (5.6)	Resists the impact without any functional deterioration. (4.4.6)	✓
Water retention	Watertightness. (5.7)	Retains water. (4.4.7)	✓

QUALITY CERTIFICATES:

kiwa CERTIFICADO ISO 14001 1918-9/23 ENAC
kiwa CERTIFICADO ISO 14006 1918-Z/22
kiwa CERTIFICADO ISO 56001 004/2008 ENAC
kiwa CERTIFICADO ISO 9001 1918-3/23 ENAC

MODEL EXAMPLE:



Konvert

PRODUCT DATA SHEET

profiltek®


WARNINGS!


/ For standard height of 1950 mm.
/ Minimum wardrobe door width FS= 300 mm. Maximum wardrobe door width FS=1000 mm.
/ Compensation for fixed wardrobe separator: 20 mm.
/ The base price includes 3 height-adjustable shelves in Transparent finish as standard, Lima handle as standard, and the wardrobe door and space separator in Acid finish.
/ In the case of optional fixed shelves, 2 fixed shelves and 1 top panel will be supplied.
/ Shelf dimensions will depend on the wardrobe's width and depth.
/ For Gold, Copper, Champagne and Gunmetal finishes, the internal fittings and zip mechanism of the wardrobe will be supplied in Black finish.
/ Standard transparent gaskets. For Black frame finish, option of Black gaskets available at extra cost.
/ The shower enclosure closure will always be made against the fixed wardrobe separator.
/ Konvert tray can only be cut lengthwise in the wardrobe area (FS). The Konvert tray is custom-made by trimming the wardrobe section while keeping the shower enclosure section (E) fixed. Cutting the tray on site is recommended.
/ Konvert configurations (shower enclosure + wardrobe) are only available for Konvert trays. Profiltek accepts no responsibility for using this combination with any other tray model.
/ Shower space side (E) must be specified on the order.
/ Minimum glass width for Imagik: 250 mm.
/ Custom Imagik. Technical feasibility of your proposal must be checked.
/ See optional shower tray accessories in the shower tray catalogue.
/ VAT excluded.


Technical details

*The plans and dimensions shown correspond to the standard product configuration. Any modification to the configuration may affect these dimensions.

Closing types


Contact closure


Contact closure


Contact closure