


AVAILABLE MODELS:



COMMON FEATURES OF THE SERIES:

- Shower enclosure with hinged panels.
- 6 mm safety glass.
- Profile finishes in White, Polished Silver, Chrome and Black.
- Base profile in Chrome and Black finish.
- Nantes handle in Chrome and Black finish as standard.
- 20 mm profile offset on each side.
- Equipped with base profile and magnetic lock.
- Magnetic hinge that ensures 180° folding panel alignment.
- Rubber watertightness system in hinge profile.
- Teknoclean as standard.

FINISHES:

- Anodized profiles in white, black y polished silver.

COMPOSITION/MATERIALS:

Profiles:Aluminium. Alloy 6063
Metallic pieces:Zamak, Steel
Chromed plastic covers:ABS
Transparent plastic lids:ABS
Rollers:Steel ball bearings, brass inside track, POM outside track
Seals:PVC

TESTS:

The PMR collection complies with the European standard EN 14428, exceeding all the tests stipulated therein, as detailed below.

Characteristic to be tested	Assessment method	Compliance criteria	Apt
Cleanability	Visual examination. (4.2)	Free from sharp corners, edges and burrs. (4.2)	✓
Impact resistance / shatter properties	R100, 40 particles minimum. (5.1, 5.2)	Thermally toughened safety glass. (4.3)	✓
Corrosion resistance	240 hours in salt spray. (4.4.2)	Corrosion-proof. (4.4.2)	✓
Resistance to chemicals and stains	Reagents: acids, alkalis, alcohols,bleaches, staining agents. (5.3)	Not showing permanent staining or deterioration. (4.4.3)	✓
Resistance to wet and dry cycling	Wet and dry 50 cycles. (5.4)	Not showing any cracks, crazing or discoloration after 50 cycles. (4.4.4)	✓
Endurance	20.000 closing-opening cycles. (5.5)	Not showing any functional deterioration. (4.4.5)	✓
Stability	Resistance to impact. (5.6)	Resists the impact without any functional deterioration. (4.4.6)	✓
Water retention	Watertightness. (5.7)	Retains water. (4.4.7)	✓

QUALITY CERTIFICATES:




MODEL EXAMPLE:



WARNINGS!

- / Standard height for models AS-232, AS-236, AS-239 and AS-230: 1950 mm.
- / Standard height for models AS-210 and AS-218: 800 mm.
- / Angled profile available subject to prior technical feasibility study.
- / Folding panels supplied to equal size.
- / Anchorage side must be specified on the order.
- / Lower door on models AS-232, AS-236, AS-239 and AS-230 has a total height of 800 mm.
- / For models combining fixed and sliding panels, include measurements for each.
- / This series does not accept Imagik or Satinado finishes.
- / Any glass over 1200 mm or top tracks and profiles over 2200 mm will incur an additional surcharge due to special logistics. See "surcharges" on page 23.
- / VAT excluded.

Technical details



*The plans and dimensions shown correspond to the standard product configuration. Any modification to the configuration may affect these dimensions.

Closing types

