
Versatil Hinged

PRODUCT DATA SHEET

profiltek®

AVAILABLE MODELS:



VRB-205 VRB-206 VRB-207 VRB-208 VRB-210 VRB-213 VRB-216 VRB-220

COMMON FEATURES OF THE SERIES:

- Bath and shower screen with hinged models.
- Outward opening.
- 6 or 8 mm toughened safety glass.
- Profile finishes in Chrome, Polished Silver, Black, Gold, Copper, Champagne and Gunmetal.
- Niza handle as standard.
- Hinges and brackets with +5 mm adjustment.
- Fixed panels with wall profile featuring +15 mm adjustment.
- Door lift and position memory system.
- New patented hinge adjustment system.
- Magnetic closure as standard. Contact closure optional.
- Eco-designed product.
- Teknoclean included.

FINISHES:

- Anodized profiles in champagne, gold, black, polished silver y copper.

COMPOSITION/MATERIALS:

Profiles: ..... Aluminium. Alloy 6063
Metallic pieces: ..... Zamak, Steel
Chromed plastic covers: ..... ABS
Transparent plastic lids: ..... ABS
Rollers: ..... Steel ball bearings, brass inside track, POM outside track
Seals: ..... PVC

TESTS:

The VERSATIL HINGED collection complies with the European standard EN 14428, exceeding all the tests stipulated therein, as detailed below.

Characteristic to be tested	Assessment method	Compliance criteria	Apt
Cleanability	Visual examination. (4.2)	Free from sharp corners, edges and burrs. (4.2)	✓
Impact resistance / shatter properties	R100, 40 particles minimum. (5.1, 5.2)	Thermally toughened safety glass. (4.3)	✓
Corrosion resistance	240 hours in salt spray. (4.4.2)	Corrosion-proof. (4.4.2)	✓
Resistance to chemicals and stains	Reagents: acids, alkalis, alcohols,bleaches, staining agents. (5.3)	Not showing permanent staining or deterioration. (4.4.3)	✓
Resistance to wet and dry cycling	Wet and dry 50 cycles. (5.4)	Not showing any cracks, crazing or discoloration after 50 cycles. (4.4.4)	✓
Endurance	20.000 closing-opening cycles. (5.5)	Not showing any functional deterioration. (4.4.5)	✓
Stability	Resistance to impact. (5.6)	Resists the impact without any functional deterioration. (4.4.6)	✓
Water retention	Watertightness. (5.7)	Retains water. (4.4.7)	✓

QUALITY CERTIFICATES:

kiwa CERTIFICADO ISO 14001 1918-9/23 ENAC
kiwa CERTIFICADO ISO 14006 1918-Z/22
kiwa CERTIFICADO ISO 56001 004/2008 ENAC
kiwa CERTIFICADO ISO 9001 1918-3/23 ENAC

MODEL EXAMPLE:



Versatil Hinged

PRODUCT DATA SHEET


profiltek®

WARNINGS!


/ Maximum height: 2200 mm. In Chrome finish, maximum height: 2000 mm. For Wavy glass finish, maximum height: 2000 mm.
/ It is essential to indicate the fixing side in the order.
/ The setback of the shower enclosure is determined by the exterior of the base profile.
/ See closure types according to configuration in the configurator.
/ For shower enclosures with a height under 1650 mm, the handle/knob height will be 600 mm. For enclosures taller than 1650 mm, the handle will be centred on the glass.
/ Minimum glass width for Imagik: 250 mm, depending on configuration. See pricing footnote.
/ Custom Imagik available. Consult the technical feasibility of your proposal.
/ Any glass wider than 1200 mm or guides and profiles longer than 2200 mm will incur an additional surcharge due to special logistics. See ßrice surcharges"on page 23.
/ No surcharge applies for a bathtub height of 1500 mm.
/ VAT not included.

Technical details


VRB-205




VRB-206




VRB-207




VRB-208




VRB-210




VRB-213



VRB-216




VRB-220




*The plans and dimensions shown correspond to the standard product configuration. Any modification to the configuration may affect these dimensions.


Closing types




Magnetic closure




Profile with magnetic closure



Magnetic closure



Magnetic closure



Contact closure