Versátil Hinged Profile

PRODUCT DATA SHEET

profiltek®

AVAILABLE MODELS:

COMMON FEATURES OF THE SERIES:

- Bath and shower screen for bathtub with hinged panel models featuring frame.
- Option for inward and outward opening.
- 6 or 8 mm toughened safety glass for Versátil Plus and 6 mm for Versátil Lite.
- Profile finishes in Chrome, Polished Silver, Black, Gold, Copper, Champagne and Gunmetal.
- Perimeter bar and XL handle as standard on Versátil Plus models. Multi-position bar and Niza knob as standard on Versátil Lite models.
- Option to cut the XL handle to size.
- +15 mm adjustment per side on fixed panels or doors.
- Lifting system and door position memory.
- Patented magnetic sealing system.
- Magnetic closure as standard. Non-magnetic contact closure optional.
- Easy installation, minimising silicone use.
- Eco-designed product.
- Teknoclean included.

FINISHES:

- Anodized profiles in champagne, gold, black, polished silver y copper.

COMPOSITION/MATERIALS:

Profiles: ..... Aluminium. Alloy 6063
Metallic pieces: ..... Zamak, Steel
Chromed plastic covers: ..... ABS
Transparent plastic lids: ..... ABS
Rollers: ..... Steel ball bearings, brass inside track, POM outside track
Seals: ..... PVC

TESTS:

The VERSÁTIL HINGED PROFILE collection complies with the European standard EN 14428, exceeding all the tests stipulated therein, as detailed below.

Characteristic to be tested	Assessment method	Compliance criteria	Apt
Cleanability	Visual examination. (4.2)	Free from sharp corners, edges and burrs. (4.2)	✓
Impact resistance / shatter properties	R100, 40 particles minimum. (5.1, 5.2)	Thermally toughened safety glass. (4.3)	✓
Corrosion resistance	240 hours in salt spray. (4.4.2)	Corrosion-proof. (4.4.2)	✓
Resistance to chemicals and stains	Reagents: acids, alkalis, alcohols,bleaches, staining agents. (5.3)	Not showing permanent staining or deterioration. (4.4.3)	✓
Resistance to wet and dry cycling	Wet and dry 50 cycles. (5.4)	Not showing any cracks, crazing or discoloration after 50 cycles. (4.4.4)	✓
Endurance	20.000 closing-opening cycles. (5.5)	Not showing any functional deterioration. (4.4.5)	✓
Stability	Resistance to impact. (5.6)	Resists the impact without any functional deterioration. (4.4.6)	✓
Water retention	Watertightness. (5.7)	Retains water. (4.4.7)	✓

QUALITY CERTIFICATES:

kiwa CERTIFICADO ISO 14001 1918-9/23 ENAC
kiwa CERTIFICADO ISO 14006 1918-Z/22
kiwa CERTIFICADO ISO 56001 004/2008 ENAC
kiwa CERTIFICADO ISO 9001 1918-3/23 ENAC

MODEL EXAMPLE:



Versátil Hinged Profile


PRODUCT DATA SHEET

WARNINGS!


/ Maximum height: 2200 mm. In Chrome finish, maximum height: 2000 mm. For Wavy glass finish, maximum height: 2000 mm.
/ It is essential to indicate the fixing side side in the order.
/ The setback of the shower enclosure is determined by the exterior of the base profile.
/ See closure types according to configuration in the configurator.
/ For shower enclosures with a height under 1650 mm, the knob height will be 600 mm. For enclosures taller than 1650 mm, the knob will be centered on the glass.
/ Option to cut the XL handle to size.
/ Minimum glass width for Imagik: 250 mm, depending on configuration. See pricing footnote.
/ Custom Imagik available. Consult the technical feasibility of your proposal.
/ Any glass wider than 1200 mm or guides and profiles longer than 2200 mm will incur an additional surcharge due to special logistics. See ßrice surcharges"on page 23.
/ No surcharge applies for a bathtub height of 1500 mm.
/ VAT not included.

Technical details


VR PLUS-210




VR LITE-210




VR LITE-206




VR PLUS-206




VR PLUS-205




VR PLUS-207




VR PLUS-216




VR LITE-205




VR LITE-207




VR LITE-216




VR PLUS-208




VR PLUS-213




VR PLUS-220




VR PLUS-240




VR LITE-208




VR LITE-213




VR LITE-220




VR LITE-240




VR LITE-106




VR LITE-110



VR LITE-209




VR PLUS-209




*The plans and dimensions shown correspond to the standard product configuration. Any modification to the configuration may affect these dimensions.


Closing types




Profile with magnetic closure




Profile with magnetic closure



Profile with magnetic closure



Profile with magnetic closure



Contact closure