

Versátil Hinged Profile

PRODUCT DATA SHEET

profiltek®

AVAILABLE MODELS:

COMMON FEATURES OF THE SERIES:

- Bath and shower screen for bathtub with hinged panel models featuring frame.
- Option for inward and outward opening.
- 6 or 8 mm toughened safety glass for Versátil Plus and 6 mm for Versátil Lite.
- Profile finishes in Chrome, Polished Silver, Black, Gold, Copper, Champagne and Gunmetal.
- Perimeter bar and XL handle as standard on Versátil Plus models. Multi-position bar and Niza knob as standard on Versátil Lite models.
- Option to cut the XL handle to size.
- +15 mm adjustment per side on fixed panels or doors.
- Lifting system and door position memory.
- Patented magnetic sealing system.
- Magnetic closure as standard. Non-magnetic contact closure optional.
- Easy installation, minimising silicone use.
- Eco-designed product.
- Teknoclean included.

FINISHES:

- Anodized profiles in champagne, gold, black y copper.

COMPOSITION/MATERIALS:

Profiles:Aluminium. Alloy 6063
Metallic pieces:Zamak, Steel
Chromed plastic covers:ABS
Transparent plastic lids:ABS
Rollers:Steel ball bearings, brass inside track, POM outside track
Seals:PVC

TESTS:

The VERSÁTIL HINGED PROFILE collection complies with the European standard EN 14428, exceeding all the tests stipulated therein, as detailed below.

Characteristic to be tested	Assessment method	Compliance criteria	Apt
Cleanability	Visual examination. (4.2)	Free from sharp corners, edges and burrs. (4.2)	✓
Impact resistance / shatter properties	R100, 40 particles minimum. (5.1, 5.2)	Thermally toughened safety glass. (4.3)	✓
Corrosion resistance	240 hours in salt spray. (4.4.2)	Corrosion-proof. (4.4.2)	✓
Resistance to chemicals and stains	Reagents: acids, alkalis, alcohols,bleaches, staining agents. (5.3)	Not showing permanent staining or deterioration. (4.4.3)	✓
Resistance to wet and dry cycling	Wet and dry 50 cycles. (5.4)	Not showing any cracks, crazing or discoloration after 50 cycles. (4.4.4)	✓
Endurance	20.000 closing-opening cycles. (5.5)	Not showing any functional deterioration. (4.4.5)	✓
Stability	Resistance to impact. (5.6)	Resists the impact without any functional deterioration. (4.4.6)	✓
Water retention	Watertightness. (5.7)	Retains water. (4.4.7)	✓

QUALITY CERTIFICATES:



MODEL EXAMPLE:

