Versatil Bifold

PRODUCT DATA SHEET

profiltek®

AVAILABLE MODELS:

COMMON FEATURES OF THE SERIES:

- Folding panel screen for bathtubs and showers.
- Inward and outward opening.
- 6 mm and 8 mm safety glass for Versátil Plus and 6 mm for Versátil Lite.
- Profile finishes in Chrome, Polished Silver, Black, Gold, Copper, Champagne and Gunmetal.
- Perimeter bar and XL handle as standard for Versátil Plus models.
- Multi-position stabiliser bar and Niza knob as standard for Versátil Lite models.
- +15 mm adjustment on each side for fixed panels and doors.
- Door lifting and position memory system.
- Patented magnetic sealing system.
- Magnetic closure as standard.
- Contact closure as an option.
- Simple installation, reducing the use of silicone.
- See series optional accessories.
- Tecknoclean included.

FINISHES:

- Anodized profiles in champagne, gold, black, polished silver y copper.

COMPOSITION/MATERIALS:

Profiles: ..... Aluminium. Alloy 6063
Metallic pieces: ..... Zamak, Steel
Chromed plastic covers: ..... ABS
Transparent plastic lids: ..... ABS
Rollers: ..... Steel ball bearings, brass inside track, POM outside track
Seals: ..... PVC

TESTS:

The VERSATIL BIFOLD collection complies with the European standard EN 14428, exceeding all the tests stipulated therein, as detailed below.

Characteristic to be tested	Assessment method	Compliance criteria	Apt
Cleanability	Visual examination. (4.2)	Free from sharp corners, edges and burrs. (4.2)	✓
Impact resistance / shatter properties	R100, 40 particles minimum. (5.1, 5.2)	Thermally toughened safety glass. (4.3)	✓
Corrosion resistance	240 hours in salt spray. (4.4.2)	Corrosion-proof. (4.4.2)	✓
Resistance to chemicals and stains	Reagents: acids, alkalis, alcohols,bleaches, staining agents. (5.3)	Not showing permanent staining or deterioration. (4.4.3)	✓
Resistance to wet and dry cycling	Wet and dry 50 cycles. (5.4)	Not showing any cracks, crazing or discoloration after 50 cycles. (4.4.4)	✓
Endurance	20.000 closing-opening cycles. (5.5)	Not showing any functional deterioration. (4.4.5)	✓
Stability	Resistance to impact. (5.6)	Resists the impact without any functional deterioration. (4.4.6)	✓
Water retention	Watertightness. (5.7)	Retains water. (4.4.7)	✓

QUALITY CERTIFICATES:

kiwa CERTIFICADO ISO 14001 1918-9/23 ENAC
kiwa CERTIFICADO ISO 14006 1918-Z/22
kiwa CERTIFICADO ISO 56001 004/2008 ENAC
kiwa CERTIFICADO ISO 9001 1918-3/23 ENAC

MODEL EXAMPLE:



Versatil Bifold

PRODUCT DATA SHEET

profiltek®

WARNINGS!

/ Maximum height: 2200 mm. In Chrome finish, maximum height: 2000 mm. For Wavy glass finish, maximum height 2000 mm.
/ Anchor side must be specified on the order.
/ Shower enclosure setback determined by the outer edge of the base profile.
/ See closure types according to configuration in the designer.
/ For shower enclosures under 1650 mm height, handle height will be 600 mm. For heights over 1650 mm, the handle will be centred on the glass.
/ Minimum glass width for Imagik: 250 mm according to configuration. See price list footnote.
/ Custom Imagik. Consult technical feasibility of your proposal.
/ Any glass width over 1200 mm or guides/profiles over 2200 mm will incur an additional surcharge due to special logistics. See "price list uplifts" on page 23.
/ For bathtub height 1500 mm, NO price list uplift applies.
/ VAT excluded.

Technical details

VR LITE-218



VR LITE-219



VR PLUS-219



VR PLUS-219



VR LITE-218



VR LITE-219



*The plans and dimensions shown correspond to the standard product configuration. Any modification to the configuration may affect these dimensions.

Closing types



Profile with magnetic closure



Profile with magnetic closure



Contact closure



No closure