
Vita

PRODUCT DATA SHEET

profiltek®

AVAILABLE MODELS:



VA-210 VA-216 VA-211 VA-220 VA-225 VA-250 VA-221 VA-230

COMMON FEATURES OF THE SERIES:

- Bathtub and shower enclosure with sliding and fixed panels.
- 8 mm safety glass.
- Profile finishes in Silver, Matt White, Chrome and Black.
- Turín handle in Matt White, Chrome and Black finish as standard.
- Base profile in Matt White, Chrome and Black finish.
- 10 mm profile offset on each side.
- Bearings adjustable in height by 4 mm.
- Equipped with magnetic or contact lock according to configuration.
- Panel anti-fall system.
- Without lower guide.
- Quick mounting system.
- See series optional accessories.
- Teknoclean as standard.

FINISHES:

- Anodized profiles in black y silver.

COMPOSITION/MATERIALS:

Profiles: ..... Aluminium. Alloy 6063
Metallic pieces: ..... Zamak, Steel
Chromed plastic covers: ..... ABS
Transparent plastic lids: ..... ABS
Rollers: ..... Steel ball bearings, brass inside track, POM outside track
Seals: ..... PVC

TESTS:

The VITA collection complies with the European standard EN 14428, exceeding all the tests stipulated therein, as detailed below.

Characteristic to be tested	Assessment method	Compliance criteria	Apt
Cleanability	Visual examination. (4.2)	Free from sharp corners, edges and burrs. (4.2)	✓
Impact resistance / shatter properties	R100, 40 particles minimum. (5.1, 5.2)	Thermally toughened safety glass. (4.3)	✓
Corrosion resistance	240 hours in salt spray. (4.4.2)	Corrosion-proof. (4.4.2)	✓
Resistance to chemicals and stains	Reagents: acids, alkalis, alcohols,bleaches, staining agents. (5.3)	Not showing permanent staining or deterioration. (4.4.3)	✓
Resistance to wet and dry cycling	Wet and dry 50 cycles. (5.4)	Not showing any cracks, crazing or discoloration after 50 cycles. (4.4.4)	✓
Endurance	20.000 closing-opening cycles. (5.5)	Not showing any functional deterioration. (4.4.5)	✓
Stability	Resistance to impact. (5.6)	Resists the impact without any functional deterioration. (4.4.6)	✓
Water retention	Watertightness. (5.7)	Retains water. (4.4.7)	✓

QUALITY CERTIFICATES:

kiwa CERTIFICADO ISO 14001 1918-9/23 ENAC
kiwa CERTIFICADO ISO 14006 1918-Z/22
kiwa CERTIFICADO ISO 56001 004/2008 ENAC
kiwa CERTIFICADO ISO 9001 1918-3/23 ENAC

MODEL EXAMPLE:



Vita

PRODUCT DATA SHEET


profiltek®

WARNINGS!


/ In Chrome finish, maximum height: 2000 mm.
/ Approximate panel overlap dimension: 20 mm. Depending on installation conditions, this value may vary.
/ Angled profile available upon prior technical feasibility study.
/ The VA-210 front panel is supplied without closure profile, with the option to request it as an extra.
/ In the VA-250 model, the stabiliser bar position is fixed.
/ Standard transparent seals. For Black profile finish, Black seals available at extra cost.
/ A floor-level shower tray may cause a change in enclosure dimensions.
/ Minimum glass width for Imagik: 250 mm.
/ Custom Imagik. Technical feasibility of your proposal must be checked.
/ Any glass over 1200 mm or guides/profiles over 2200 mm will incur an additional charge due to special logistics. See "extra charges" on page 23.
/ For bath height 1500 mm, NO extra charge applies.
/ VAT excluded.

Technical details


VA-210




VA-216




VA-211




VA-220




VA-225



VA-250




VA-221




VA-230

*The plans and dimensions shown correspond to the standard product configuration. Any modification to the configuration may affect these dimensions.


Closing types




Profile with contact closure




Magnetic closure




Magnetic closure



overlap



Contact closure



Contact closure