Wind

PRODUCT DATA SHEET

profiltek®

AVAILABLE MODELS:



WI-261 WI-210 WI-220 WI-225 WI-216 WI-230

COMMON FEATURES OF THE SERIES:

- Bathtub and shower enclosure with sliding and fixed panels.
- 6 mm safety glass.
- Profile finishes in White and Silver Polished.
- Mónaco handle in Chrome finish as standard.
- Base profile in Chrome finish.
- 15 mm profile offset on each side.
- Double bearing train adjustable in height by 5 mm.
- Equipped with magnetic or contact closure according to configuration.
- Panel anti-rollover system.
- Without lower guide.
- Quick mounting system.
- See series optional accessories.
- Teknoclean as standard.

FINISHES:

- Anodized profiles in white, black y polished silver.

COMPOSITION/MATERIALS:

Profiles: ..... Aluminium. Alloy 6063
Metallic pieces: ..... Zamak, Steel
Chromed plastic covers: ..... ABS
Transparent plastic lids: ..... ABS
Rollers: ..... Steel ball bearings, brass inside track, POM outside track
Seals: ..... PVC

TESTS:

The WIND collection complies with the European standard EN 14428, exceeding all the tests stipulated therein, as detailed below.

Characteristic to be tested	Assessment method	Compliance criteria	Apt
Cleanability	Visual examination. (4.2)	Free from sharp corners, edges and burrs. (4.2)	✓
Impact resistance / shatter properties	R100, 40 particles minimum. (5.1, 5.2)	Thermally toughened safety glass. (4.3)	✓
Corrosion resistance	240 hours in salt spray. (4.4.2)	Corrosion-proof. (4.4.2)	✓
Resistance to chemicals and stains	Reagents: acids, alkalis, alcohols,bleaches, staining agents. (5.3)	Not showing permanent staining or deterioration. (4.4.3)	✓
Resistance to wet and dry cycling	Wet and dry 50 cycles. (5.4)	Not showing any cracks, crazing or discoloration after 50 cycles. (4.4.4)	✓
Endurance	20.000 closing-opening cycles. (5.5)	Not showing any functional deterioration. (4.4.5)	✓
Stability	Resistance to impact. (5.6)	Resists the impact without any functional deterioration. (4.4.6)	✓
Water retention	Watertightness. (5.7)	Retains water. (4.4.7)	✓

QUALITY CERTIFICATES:

kiwa CERTIFICADO ISO 14001 1918-9/23 ENAC
kiwa CERTIFICADO ISO 14006 1918-Z/22
kiwa CERTIFICADO ISO 56001 004/2008 ENAC
kiwa CERTIFICADO ISO 9001 1918-3/23 ENAC

MODEL EXAMPLE:



Wind

PRODUCT DATA SHEET

profiltek®

WARNINGS!

/ Maximum shower enclosure height 2200 mm.
/ Approximate panel overlap dimension 20 mm. Depending on installation conditions, this value may vary.
/ A floor-level shower tray may alter the shower enclosure dimension.
/ Minimum glass width for Imagik 250 mm.
/ Custom Imagik. Please consult technical feasibility of your proposal.
/ Maximum height of 1950 mm for model WI-261.
/ Any glass over 1200 mm or top tracks/profiles over 2200 mm will incur an additional surcharge due to special logistics. See "surcharges on price list" on page 23.
/ For bath height 1500 mm NO surcharge applies.
/ VAT excluded.

Technical details

WI-261



WI-210



WI-220



WI-225



WI-216



WI-230



*The plans and dimensions shown correspond to the standard product configuration. Any modification to the configuration may affect these dimensions.

Closing types



Profile with contact closure



Magnetic closure



Magnetic closure



Magnetic closure



overlap



Magnetic closure